

Grade : **Anti Odor**

General Purpose: Anti Odor

Main Component: Special additives and resins.

Product Features: Anti Odor is a unique additive that reduces the unpleasant odor caused by most solvents and related products. Anti Odor does not change the characteristics of the product except extending the drying time by 5 – 10%, Longer dry time required in cooler temperatures and higher humidity, so the color of product you want, you will still get. Anti Odor won't hide or cover up odors, it chemically neutralizes them when it is activated by oxygen. The molecules attach themselves to the product's vapors causing them to fall away undetected. As it reacts to the air, it completely evaporates out of the product's film taking the odor along with it. Ideal uses for Anti Odor Perfect for use on Acrylic, Urethane, Epoxy, Oil, Alkyd, Water based paints etc. Ideal for use in sensitive areas such as bedrooms. Formulated to effectively reduce paint odors by up to 90%, Anti Odor gives you a very high comfort level.

Application: It is suitable for use in almost all paints, stains, primers, epoxy, recycled oils, urethane, varnish, solvents, enamels, glues, adhesives and other surface coatings.

Recommended dosage: 0.005%-0.015 for medium odor such as alcohols
0.015%-0.2% for heavy odor such as aromatics, oil and etc.

Typical values

Solid by Weight 77.9%

Solid by Volume 53.3%

Viscosity 75 – 85 *cst*

Flash Point 102°F(38.9°C)

Dry Time @20°C